

Lanyard Anchorage

Complies with AS/NZ 1891

C210



CAUTION

WHEN SETTING THE OUTRIGGERS,
SET THE MAIN OUTRIGGERS FIRST.
THEN SET THE 5th FRONT JACK.

WHEN RESTOWING THE OUTRIGGERS,
ALWAYS LIFT THE 5th FRONT JACK FIRST

C207

OUTRIGGER

BEAM

LOCK

C206



WARNING

'ACCESS ISOLATOR TRAVERSE MOTION ONLY'

'THIS ISOLATOR DOES NOT ISOLATE THE
CRANE FROM IT'S POWER SOURCE'

W305

TRAVEL LOCK PIN

C204

POWER TAKE-OFF

PULL AFTER SETTING THE SHIFT
LEVER TO NEUTRAL POSITION



C209

CRANE USE LOCK PIN

C205



WARNING

**NOT TO BE
OPERATED BY
UNAUTHORISED
PERSONS**

W307

FRONT END LOADER CONTROLS

DOWN

↑
ARMS

↓
UP

DUMP

↑
BUCKET

↓
CROWD

CLOSE

↑
BUCKET

↓
OPEN

G141

Unauthorised persons are
warned to keep out of
working range of crane

EMERGENCY STOP

D236

WARNING

WHENEVER PRACTICAL, CRANE USE MUST BE
CONTROLLED FROM THE OPPOSITE SIDE OF THE
VEHICLE FROM WHERE THE CRANE IS OPERATING.

W315

LIFTING POINT

W319

ENGINE OIL

G140